



SDS

Safety Data Sheet

Shaw of Australia Pty Ltd

SheerWeave Style 7400 Blackout Fabric

SDS Number: PI-SDS-T675

Revision Date: 2/29/2016

Page 1 of 4

1

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Shaw of Australia Pty Ltd
www.shawaust.com.au

Vendor

Phifer, Inc.
4400 Kauloosa Ave.
Tuscaloosa, AL 35401

Phone:

205/345-2120

Web:

www.Phifer.com

Product Name: SheerWeave Style 7400 Blackout Fabric
Revision Date: 2/29/2016
Version: 1
SDS Number: PI-SDS-T675
Product Code: PI-SDS-T675
Product Use: Window Shades

2

HAZARDS IDENTIFICATION

Route of Entry:

Eyes; Ingestion; Inhalation; Skin

Inhalation: Short-term harmful health affects are not expected from vapor generated during normal use at ambient temperature.

Skin Contact: May cause irritation.

Eye Contact: May cause irritation.

Ingestion: Consult physician

GHS Precautionary Statements:

P281 - Use personal protective equipment as required.

P337 - If eye irritation persists: flush with water



SDS

Safety Data Sheet Shaw of Australia Pty Ltd

SheerWeave Style 7400 Blackout Fabric

SDS Number: PI-SDS-T675

Revision Date: 2/29/2016

Page 2 of 4

3 COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

	<u>WT. %</u>	<u>CAS Registry #</u>
Polyester	95-100	NA
Acrylic Foamed Backing	0-5	NA

OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200):

OSHA EXPOSURE LIMITS 8 hrs. TWA (ppm)

	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Polyester:	no restriction	--
Acrylic Foamed Backing	not determined	--

4 FIRST AID MEASURES

Inhalation: If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.

Skin Contact: Promptly flush skin with water.

Eye Contact: Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate irrigation.

Ingestion: Not a direct hazard.

5 FIRE FIGHTING MEASURES

Flash Point: N/A

Flash Point Method: N/A

Autoignition Temp: N/A

LEL: N/A

UEL: N/A

Use foam, dry chemical, or water fog.

Wear SCBA and appropriate PPE when exposed to products of decomposition.

6 ACCIDENTAL RELEASE MEASURES

This product requires no special spill handling procedures.

7 HANDLING AND STORAGE

Handling Precautions: Keep away from sources of ignition.

Storage Requirements: Store at ambient temperature at atmospheric pressure.



SheerWeave Style 7400 Blackout Fabric

SDS Number: PI-SDS-T675

Revision Date: 2/29/2016

Page 3 of 4

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: General mechanical room ventilation is expected to be satisfactory.

Personal Protective Equip: Not required for intended use.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Textured fabric of varying colors with an off-white acrylic foamed backing.
Physical State: Solid
Solubility: Insoluble in water
Viscosity: Solid

10 STABILITY AND REACTIVITY

Stability: Product is stable under normal conditions.
Conditions to Avoid: None known
Materials to Avoid: Strong Oxidizing Agents.
Hazardous Decomposition: N/A
Hazardous Polymerization: Will not occur.

11 TOXICOLOGICAL INFORMATION

Data not available

12 ECOLOGICAL INFORMATION

Data not available

13 DISPOSAL CONSIDERATIONS

If this product becomes a waste, it DOES NOT meet the criteria of a hazardous waste as defined under 40 CFR 261, in that it does not exhibit the characteristics of hazardous waste of Subpart C, nor is it listed as a hazardous waste under Subpart D.

As a non-hazardous waste, it should be disposed of in accordance with local, state and federal regulations.



SDS

Safety Data Sheet Shaw of Australia Pty Ltd

SheerWeave Style 7400 Blackout Fabric

SDS Number: PI-SDS-T675

Revision Date: 2/29/2016

Page 4 of 4

14

TRANSPORT INFORMATION

DOT Class: Not regulated #

Not regulated by DOT.

15

REGULATORY INFORMATION

TSCA (Toxic Substance Control Act)

Components of this product are listed on the TSCA inventory.

CERCLA (Comprehensive Response Compensation, and Liability Act)

NOT reportable

SARA TITLE III (Superfund Amendments and Reauthorization Act)

313/312 Hazard categories:

None.

313 Reportable Ingredients:

None.

16

OTHER INFORMATION

THE INFORMATION IN THIS SAFETY DATA SHEET SHOULD BE PROVIDED TO ALL WHO WILL USE, HANDLE, STORE, TRANSPORT, OR OTHERWISE BE EXPOSED TO THIS PRODUCT. THIS INFORMATION HAS BEEN PREPARED FOR THE GUIDANCE OF PLANT ENGINEERING, OPERATIONS AND MANAGEMENT AND FOR PERSONS WORKING WITH OR HANDLING THIS PRODUCT. PHIFER INCORPORATED BELIEVES THIS INFORMATION TO BE RELIABLE AND UP-TO-DATE AS OF THE DATE OF PUBLICATION, BUT MAKES NO WARRANTY THAT IT IS. ADDITIONALLY, IF THIS SAFETY DATA SHEET IS MORE THAN THREE YEARS OLD, YOU SHOULD CONTACT PHIFER INCORPORATED AT THE NUMBER LISTED BELOW TO MAKE CERTAIN THAT THIS SHEET IS CURRENT.

PHIFER INCORPORATED
P.O. BOX 1700
TUSCALOOSA, AL 35403

(205) 345-2120



PRODUCT CERTIFIED FOR
LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818