

SheerWeave® Style SW7000

Room Darkening Fabric




SW7000-Q00
Merino




SW7000-V70
Porpoise



SW7000-V41
Canyon



SW7000-V39
Graphite



SW7000-P63
Birch




SW7000-P64
Sand




SW7000-Q57
Wheat



SW7000-U67
Canvas




SW7000-Q58
Mushroom



SW7000-U69
Cocoa



SW7000-P62
White



SW7000-V40
Onyx

Digital sample of actual colors may vary slightly.



SheerWeave® Style SW7000 Room Darkening Fabric

SheerWeave® 7000 is uniquely designed to provide total privacy when complete room darkening is needed. With a broad range of decorator colors, the look and feel of rich cloth and a PVC-free composition, Style 7000 will enhance the beauty and function of both commercial and residential spaces. All Style 7000 colors have an off-white backing.

SHEERWEAVE STYLE 7000 BLACKOUT

WIDTHS	94" and 118" (238.8cm and 300cm)	FABRIC THICKNESS	0.029" (0.74 mm)
ROLL LENGTH	30 Linear Yards (27.4 lm)	OPENNESS FACTOR	Opaque
COMPOSITION	100% Polyester with Acrylic Flocked Backing	ACOUSTICAL VALUE	NRC 0.10 / SAA 0.08
MESH WEIGHT	12.4 oz/yd ² (420.43 g/m ²)	ACOUSTICAL PERFORMANCE	NRC (Noise Reduction Coefficient) and SAA (Sound Absorption Average) tested in accordance with ASTM C423-09a.

SPECIFICATIONS

FIRE CLASSIFICATION	California U.S. Title 19 (small scale), NFPA 701 TM#1 (small scale), BS 5867 Part 2 Type B Performance, CAN/ULC-S 109 (large and small scale), CAN/CGSB2-4.162-M80, IBC Section 803.1.1 (Class A Rating), NFPA 101 (Class A Rating). Fire classifications are subject to change. Please visit phifer.com for the most current information.
BACTERIA AND FUNGAL RESISTANCE	ASTM G21
ENVIRONMENTAL CERTIFICATION	Certified to GREENGUARD and GREENGUARD Gold standards for low chemical emissions into indoor air during product usage.
SAFE USE	RoHS Compliant, US Consumer Product Safety Commission Section 101 and ANSI/WCMA A 100.1-2007 for lead content.
Standard Uses	Roller shades & panel tracks.
UV Protection	SheerWeave sun control fabrics are an effective way to reduce harmful UV rays. Phifer Incorporated is a proud member of the Skin Cancer Foundation's Corporate Council.
Warranty	5-year interior.
CLEANING INSTRUCTIONS	Fabric should be regularly dusted/vacuumed as appropriate. If commercial spot cleaners are used, they must first be tested and allowed to dry on an inconspicuous area to ensure compatibility.

TECHNICAL DATA

CODE / COLOR	SOLAR OPTICAL PROPERTIES				SHGC/G VALUE g-tot (glass & blind) Single Insulating	
	TS	RS	AS	TV	1/4 CL	1 HA
P63 Birch	0	74	26	0	0.21	0.18
Q00 Merino	0	72	28	0	0.23	0.19
Q57 Wheat	0	75	25	0	0.21	0.18
U67 Canvas	0	73	27	0	0.22	0.19
P62 White	0	74	26	0	0.21	0.18
P64 Sand	0	73	27	0	0.22	0.19
Q58 Mushroom	0	70	30	0	0.23	0.20
U69 Cocoa	0	72	28	0	0.23	0.19
V41 Canyon	0	74	26	0	0.21	0.19
V39 Graphite	0	71	29	0	0.23	0.19
V70 Porpoise	0	73	27	0	0.22	0.19
V40 Onyx	0	72	28	0	0.23	0.19



Railroading this fabric is not recommended.



*TS - Solar Transmittance, RS - Solar Reflectance, AS - Solar Absorptance, TV - Visual Transmittance *SHGC = Solar Heat Gain Coefficient *1/4 CL = 1/4" Clear Glass, 1 HA = 1" Heat Absorbing Glass *Fabrics Installed Internally, Zero-Degree Profile Angle *Solar Heat Gain Coefficient (SHGC) shown calculated according to Office of Building Technology, State and Community Programs, Energy Efficiency and Renewable Energy, U.S. Department of Energy's definition of SHGC. SHGC represents the percentage of solar heat gain that is transmitted to the interior through the glass and shading system. If you are using glass whose performance is listed in terms of SC, you may convert to SHGC by multiplying the SC by 0.87.



411 S. Pearl Street | Spiceland, IN 47385
765.987.7999 | 800.238.7999

draperinc.com

For additional information, questions, or to request fabric samples, please contact your Draper sales representative or scan to visit request.draperinc.com



© SheerWeave is a registered trademark of PHIFER INCORPORATED. TM UL, the UL logos and the UL mark are trademarks of UL LLC. © PHIFER INCORPORATED 0923